



Radial Type Choke Inductors PK2W0507 Series



PK2W0507 Series ,Contain high-frequency ferrite.
Comparatively large rated current. Power supplies,DC-DC converters. TVs,VTRs,computers. Computer Peripherals. Telephones,Air-Conditions. Home Electric Appliance. Electronic toys and games.



Unit:mm

P/N	L (uH)	Q (min)	DCR(mohm)	MAX	Isat (A)
PK2W0507-1R0M	1.0	85	14.0		3.50
PK2W0507-1R5M	1.5	85	20.0		3.00
PK2W0507-2R2M	2.2	85	20.0		2.50
PK2W0507-3R3M	3.3	85	30.0		2.00
PK2W0507-4R7M	4.7	80	40.0		1.70
PK2W0507-6R8M	6.8	75	60.0		1.30
PK2W0507-100K	10	70	80.0		1.00
PK2W0507-120K	12	70	100.0		0.98
PK2W0507-150K	15	65	110.0		0.90
PK2W0507-180K	18	50	110.0		0.80
PK2W0507-220K	22	50	120.0		0.70
PK2W0507-270K	27	50	140.0		0.60
PK2W0507-330K	33	50	160.0		0.55
PK2W0507-390K	39	45	180.0		0.50
PK2W0507-470K	47	45	200.0		0.50
PK2W0507-560K	56	35	220.0		0.45
PK2W0507-680K	68	35	300.0		0.45
PK2W0507-820K	82	35	340.0		0.40
PK2W0507-101K	100	20	360.0		0.40
PK2W0507-121K	120	20	440.0		0.35
PK2W0507-151K	150	20	520.0		0.30
PK2W0507-181K	180	20	650.0		0.30
PK2W0507-221K	220	20	750.0		0.25
PK2W0507-271K	270	25	100.0		0.24
PK2W0507-331K	330	25	1300.0		0.20
PK2W0507-391K	390	25	1400.0		0.18
PK2W0507-471K	470	25	1600.0		0.16
PK2W0507-561K	560	25	2000.0		0.16
PK2W0507-681K	680	25	2300.0		0.14
PK2W0507-821K	820	25	2700.0		0.13
PK2W0507-102K	1000	50	3100.0		0.12
PK2W0507-122K	1200	65	4600.0		0.11
PK2W0507-152K	1500	65	5300.0		0.10
PK2W0507-182K	1800	65	6200.0		0.09
PK2W0507-222K	2200	65	6800.0		0.08
PK2W0507-272K	2700	80	10000.0		0.06
PK2W0507-332K	3300	75	12000.0		0.06
PK2W0507-392K	3900	70	13000.0		0.055
PK2W0507-472K	4700	65	15000.0		0.055
PK2W0507-562K	5600	65	22000.0		0.050
PK2W0507-682K	6800	65	25000.0		0.045
PK2W0507-822K	8200	65	28000.0		0.045
PK2W0507-103K	10000	65	35000.0		0.035
PK2W0507-123K	12000	65	45000.0		0.030
PK2W0507-153K	15000	65	52000.0		0.030
PK2W0507-183K	18000	65	58000.0		0.030
PK2W0507-223K	22000	65	80000.0		0.020
PK2W0507-273K	27000	65	90000.0		0.020
PK2W0507-333K	33000	55	135000.0		0.015
PK2W0507-393K	39000	55	150000.0		0.015
PK2W0507-473K	47000	55	170000.0		0.015

1. Inductance tested at 2.52MHz,0.1V;
2. SRF>13MHz measured using Agilent / HP8753D network Analyzer;
3. Inductance drop = 10% typ. at rated Isat;
4. $\Delta T=40^{\circ}C$ rise typ. at Irms;
5. Operating temperature range $-20^{\circ}C$ to $+105^{\circ}C$;
6. Electrical specifications at $+25^{\circ}C$;

In Bulk Packing

Special inquiries besides the above common used types can be met on your requirement.

FENFA ELECTRONICS LTD.

Address: Rm 621, 6/F., Shing Yip Industrial Building,
19-21 Shing Yip Street, Kwun Tong, Hong Kong
Tel: (852) 2372 0880, Fax: (852) 2372 0131

<http://www.coilsfenfa.com>

fenfa@coilsfenfa.com

FENFA ELECTRONICS (DONGGUAN) CO., LTD.

Address: Xiakeng Industrial District, Changping Town,
Dongguan City, Guangdong, China
Tel: 86-769-86291668 Fax: 86-769-83999028